



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
28.01.2004 Bulletin 2004/05

(51) Int Cl.7: **B60R 21/16**

(21) Application number: 03015531.1

(22) Date of filing: 10.07.2003

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IT LI LU MC NL PT RO SE SI SK TR
Designated Extension States:
AL LT LV MK

(72) Inventors:

- **Tanaka, Tadashi**
Minato-ku, Tokyo 106-8510 (JP)
- **Kumagai, Masayoshi**
Minato-ku, Tokyo 106-8510 (JP)

(30) Priority: 22.07.2002 JP 2002212693

(74) Representative:
Banzer, Hans-Jörg, Dipl.-Ing. et al
Kraus & Weisert
Patent- und Rechtsanwälte
Thomas-Wimmer-Ring 15
80539 München (DE)

(71) Applicant: TAKATA CORPORATION
Minato-ku, Tokyo 106-8510 (JP)

(54) Guide member for curtain airbag

(57) In order to provide a guide member for a certain airbag which can be installed to a vehicle body very easily, a guide member (8) includes a rod-shaped guide (9) extending vertically relative to the vehicle body along a C pillar (7), upper and lower fixing sections (10, 11) for fixing the upper and lower ends of the guide (9) to the C pillar (7), respectively, and temporarily tacking sections (12, 13) for tacking the upper and lower fixing sections (10, 11) to the C pillar (7), respectively, when the guide member (8) is mounted to the C pillar (7). The C pillar (7) has temporarily-tacking-section insertion openings (23, 24) corresponding to the temporarily tacking sections (12, 13), respectively. When the guide member (8) is mounted to the C pillar (7), the temporarily tacking sections (12, 13) are inserted into the corresponding temporarily-tacking-section insertion openings (23, 24) for engagement, so that the guide member (8) can be temporarily tacked to the C pillar (7).




Fig. 1

Description**[Technical Field of the Invention]**

[0001] The present invention relates to a guide member for guiding a curtain airbag (curtain-like airbag) which is deployed along the side structure of the compartment of a vehicle, and more specifically, concerns a guide member mounted to a pillar of the vehicle for guiding the longitudinal ends of the curtain airbag.

[Description of the Related Art]

[0002] In automobiles equipped with curtain airbag systems, the curtain airbag is inflated downward relative to a vehicle body along the side structure (such as a door and a pillar) of the compartment in the event of a side impact or rollover to protect the head of an occupant and to prevent the occupant from being thrown out of the vehicle when a window opens.

[0003] United States Patent No. 6,237,938 discloses to provide a C pillar with a guide member for guiding the rear end of the curtain airbag, which is inflated along the side structure of the compartment, downward relative to the vehicle body and along the pillar.

[0004] The guide member disclosed in the patent includes a box-section member called a track and a slider member arranged in the track and called an element movable along the length of the track, the rear end of the curtain airbag being connected to the element. Also there are provided latches arranged at equal intervals substantially over the whole length of the track to prevent the rear end of the curtain airbag, which has moved downward, from returning upward.

[0005] The track has mounting flanges at the upper and lower ends, each flange being mounted to the C pillar with a bolt or a screw.

[Problems to be Solved by the Invention]

[0006] When mounting the guide member to the pillar with bolts or screws, as described above, a worker must hold the guide member by one hand and handle a tool by the other hand to rotate the bolts or screws, thus having low working efficiency. When the worker moves the one hand off the guide member during the bolting or screwing operation, the guide member may be rotated together with the bolts or screws.

[0007] It is an object of the present invention to solve the above problems and to provide a guide member for a curtain airbag having remarkably high vehicle-installation efficiency.

[0008] It is another object of the invention to provide a guide member capable of mooring the end of a curtain airbag that has move downward along the guide member.

[Means for Solving the Problems]

[0009] These objects are achieved by a guide member as defined in claim 1 or claim 4. The dependent claims define preferred and advantageous embodiments of the invention. The guide member for a curtain airbag according to an aspect of the present invention is a guide member for guiding the longitudinal ends of the curtain airbag that is deployed downward along the side structure of the compartment of a vehicle, wherein in the guide member for the curtain airbag extending vertically and mounted to a pillar of the vehicle, each of the upper part and the lower part of the guide member has a temporarily tacking section for tacking the guide member to the pillar.

[0010] Since such the guide member can bring the temporarily tacking section into engagement with the vehicle body for temporal tacking, a vehicle installation work is simplified.

[0011] Since the temporarily tacking section is provided to each of the upper part and the lower part of the guide member, when the guide member is fixed to the body with bolts or screws, the guide member is not rotated together with the bolts or screws.

[0012] Preferably, each of the temporarily tacking sections extends outward in a direction intersecting the longitudinal direction of the guide member. In such a case, providing the vehicle body with openings that correspond to the temporarily tacking sections allows the guide member to be temporarily tacked only by inserting the temporarily tacking sections into the openings.

[0013] The invention may have a mooring section at the end of the curtain airbag, which is formed such that the lower part of the guide member is bent or curved, so as to prevent the ends of the curtain airbag which has moved downward along the guide member from returning upward. Providing the guide member with the mooring section formed of a bent or curved portion is remarkably simple as compared with forming a latch as in US Patent No. 6,237, 938, thus reducing the cost of manufacturing the guide member.

[0014] A guide member for a curtain airbag according to another aspect of the invention is a guide member for guiding the longitudinal ends of the curtain airbag which is deployed downward along the side structure of the compartment of a vehicle, wherein in the guide member for the curtain airbag extending vertically and mounted to a pillar of the vehicle, a mooring section at the end of the curtain airbag is formed such that the lower part of the guide member is bent or curved so as to prevent the ends of the curtain airbag which has moved downward along the guide member from returning upward.

[0015] The guide member for the curtain airbag prevents the ends of the curtain airbag from returning upward, as described above. The guide member has a simple structure and can be manufactured at low cost.

[Brief Description of the Drawings]

[0016]

Fig. 1 is an exploded perspective view of a guide member for a curtain airbag according to an embodiment of the present invention.

Fig. 2 is a sectional view taken along line II-II of Fig. 1.

Fig. 3 is a perspective view showing a deployment behavior of the curtain airbag.

Fig. 4 is a perspective view of the vicinity of the upper part of a guide member for a curtain airbag according to another embodiment of the present invention.

Fig. 5 is a perspective view of another embodiment.

Fig. 6 is a perspective view of still another embodiment.

[Description of the Embodiments]

[0017] Embodiments of the present invention will be specifically described with reference to the drawings.

[0018] Fig. 1 is an exploded perspective view of a guide member for a curtain airbag according to an embodiment of the present invention. Fig. 2 is a sectional view taken along line II-II of Fig. 1. Figs. 3(a) and (b) are perspective views of the curtain airbag in a folded condition and in a fully inflated condition, respectively.

[0019] In the embodiment, a curtain airbag 1 is arranged along a roof side (a boundary between the ceiling and the side of the compartment) 2 of a vehicle in a longitudinally-folded long thin state. The curtain airbag 1 is inflated by a gas from an inflator (not shown) in the event of a side impact or rollover of the vehicle, and is deployed downward relative to the vehicle along the side structure of the compartment such as a door and a pillar. The curtain airbag 1 has a tab 3 at the upper edge, wherein a bolt 5 (see Fig. 3) is inserted into a bolt insertion hole 4 of the tab 3, and is in turn screwed into a female screw hole 6 of the roof side 2, thereby fixing the curtain airbag 1 to the roof side 2.

[0020] A C pillar 7 of the vehicle has a guide member 8 for guiding the rear end of the curtain airbag 1 along the C pillar 7 when the curtain airbag 1 is inflated downward relative to the vehicle body and along the C pillar 7. The guide member 8 includes a rod-shaped guide 9 extending vertically relative to the vehicle body and along the C pillar 7, an upper fixing section 10 and a lower fixing section 11 for fixing the upper and lower ends of the guide 9 to the C pillar 7, respectively, and temporarily tacking sections 12 and 13 for temporarily tacking the upper and lower fixing sections 10 and 11 to

the C pillar 7, respectively, when mounting the guide member 8 to the C pillar 7.

[0021] The curtain airbag 1 has a loop-like connecting band 14 in the vicinity of the lower corner at the rear end thereof. The connecting band 14 is hooked around the guide 9, so that the rear end of the curtain airbag 1 is connected to the guide member 8.

[0022] The guide 9 is formed of a pipe member. The lower part of the guide 9 is bent in substantially a crank shape, thus forming a mooring section 9a for the connecting band 14 at the L-shaped corner extending in the direction to come close to the curtain airbag 1. A substantially horizontal section 9b that connects with the mooring section 9a works as a stopper for preventing the movement of the connecting band 14 downwardly from the mooring section 9a.

[0023] The guide 9 has, at the upper and lower ends, leg-shaped sections 15 and 16 for separating the entire guide 9 from the outer surface of the C pillar 7. The leg-shaped sections 15 and 16 are formed such that the upper and lower ends of the guide 9 are bent in substantially a crank shape toward the C pillar 7. The upper and lower fixing section 10 and 11 connect with the ends of the leg-shaped sections 15 and 16, respectively.

[0024] The guide member 8 is fixed to the C pillar 7 such that bolts 19 are inserted into bolt insertion holes 17 and 18 (see Fig. 1) formed in the fixing sections 10 and 11, and are then screwed into female screw holes 20 of the C pillar 7, respectively.

The temporarily tacking sections 12 and 13 extend in the extending direction and the intersecting direction of the guide 9 so as to be inserted into the C pillar 7 through the surface at which the upper and lower fixing sections 10 and 11 overlap the C pillar 7, as shown in Fig. 2. The C pillar 7 has temporarily-tacking-section insertion openings 23 and 24 that correspond to the temporarily tacking sections 12 and 13. The upper temporarily tacking section 12 has a hook-shaped section 25 at the end, which is hooked to the lower edge of the opening 23.

[0025] In the embodiment, the hook-shaped section 25 is shaped such that the end of the upper temporarily tacking section 12 is bent downward.

[0026] The guide member 8 with such a structure can be temporarily tacked to the C pillar 7 such that the upper and lower temporarily tacking sections 12 and 13 are inserted into the corresponding temporarily-tacking-section insertion openings 23 and 24 for engagement. Therefore, there is no need to hold the guide member 8 by hand during the work such as bolting, thus remarkably simplifying installation work.

[0027] Moreover, in the embodiment, the hook-shaped section 25 provided at the end of the upper temporarily tacking section 12 is hooked to the lower edge of the opening 23. Therefore, even if a tool comes into contact with the guide member 8 during the work, the guide member 8 does not drop off the C pillar 7.

[0028] Since the temporarily tacking sections 12 and

13 are provided at the upper end and the lower end of the guide member 8, respectively, the guide member 8 is not rotated together with the bolts 19 even if the guide member 8 is not held by hand when the bolts 19 are inserted into the respective bolt insertion holes 17 and 18 of the upper and lower fixing sections 10 and 11 and are then screwed into the female screw holes 20 of the C pillar 7.

[0029] The guide member 8 mounted to the C pillar 7 guides the connecting band 14 downward when the curtain airbag 1 is inflated. In the embodiment, the guide member 8 is arranged such that an upper section 9c above the mooring section 9a comes close to the rear of the vehicle with height. Accordingly, the connecting band 14 that is the rear end of the curtain airbag 1 is prevented from returning upward when the curtain airbag 1 is guided by the guide member 8 to inflate downward relative to the vehicle body.

[0030] In other words, when inflated, the curtain airbag 1 decreases in longitudinal length by tension applied to the outer surface and the rear end is pulled forward. In the step of Fig. 3(b) in which the inflation has been completed, the connecting band 14 cannot move upward and backward along the guide 9, being held at the mooring section 9a.

[0031] In the embodiment, while the upper or lower part of the fixing sections 10 and 11 are bent toward the C pillar 7 to form the plate-like temporarily tacking sections 12 and 13, respectively, the shape and the forming method of the temporarily tacking sections are not limited to that. For example, the temporarily tacking sections may be formed such that pins or projections are attached by welding to the surfaces of the fixing sections 10 and 11 which overlap with the C pillar 7.

[0032] In the embodiment, while the temporarily tacking sections 12 and 13 and the guide member 8 are integrated, they may be separated. Fig. 4 shows an example in which each temporarily tacking section and the guide member are separately constructed. Fig. 4 is a perspective view of the vicinity of the upper part of a guide member for a curtain airbag according to another embodiment of the present invention.

[0033] A guide member 8A of Fig. 4 has a temporarily tacking member 30 at the vicinity of the upper end of the guide 9 (at the vicinity of the boundary with the leg-shaped section 15), which is constructed separately from the guide member 8A. The temporarily tacking member 30 includes a substantially-C-shaped clip 31 which is elastically in contact along the outer periphery of the guide 9 so as to hold the guide 9, a pair of extending pieces 32 and 32 which extends outward from the circumferential opposite ends of the clip 31, and a projecting temporarily tacking section 33 which extends from the side of one extending piece 32 in a direction that intersects the extending direction of the guide 9.

[0034] The similar temporarily tacking member 30 is also attached to the vicinity of the lower end of the guide 9 (at vicinity of the boundary with the leg-shaped section

16), which is not shown. The C pillar has openings in which the temporarily tacking sections 33 of the temporarily tacking member 30 can be fitted.

[0035] Other structures of the guide member 8A are the same as those of the guide member 8 of Figs. 1 to 3 except that the guide member 8 does not have the temporarily tacking sections 12 and 13 at the upper and lower fixing sections 10 and 11, respectively. In Fig. 4, the same reference numerals as those of Figs. 1 to 3 denote the same elements.

[0036] When the guide member 8A with such a structure is mounted to a C pillar (not shown), first, the clip 31 is elastically increased in diameter so as to separate both the extending pieces 32 and 32 of the temporarily tacking member 30 from each other, and the guide 9 is in turn fitted to the inner periphery of the clip 31 from between the extending pieces 32 and 32, thereby attaching the temporarily tacking members 30 to the vicinities of the upper end and the lower end of the guide 9.

[0037] Then, each temporarily tacking section 33 of the temporarily tacking member 30 is fitted to the corresponding opening (not shown) of the C pillar; thereby the guide member 8A is tacked to the C pillar; and in this state, the fixing sections 10 and 11 are fixed with bolts, so that the guide member 8A is secured to the C pillar.

[0038] Accordingly, even for the guide member 8A, there is no need to hold the guide member 8A by hand during bolting work, as for the guide member 8, and thus the guide member 8A can be mounted to the C pillar by a very simple operation. Also, when the fixing sections 10 and 11 are fixed with bolts, the guide member 8A does not rotate with the bolts, having greatly high working efficiency.

[0039] In the embodiment of Fig. 4, the temporarily tacking section 33 is a plate-like projection that linearly extends from the extending piece 32. However, it is also possible to provide a hook-shaped section at the end of the temporarily tacking section 33, in a manner similar to the temporarily tacking section 12 of the guide member 8, thereby ensuring to prevent the temporarily tacking section 33 from coming out of the opening during the temporal tacking, that is, the guide member 8A from dropping off the C pillar.

[0040] In the embodiment of Figs. 1 to 3, the mooring section 9a is formed such that the guide 9 is bent so that the lower section leans forward (near the curtain airbag 1) from the middle to the lower end longitudinally; however, the structure of the mooring section is not limited to that.

[0041] Other embodiments of the mooring section will be described hereinafter with reference to Figs. 5 and 6. Figs. 5 and 6 are perspective views of the vicinities of the C pillars to which guide members 8B and 8B' are mounted, respectively.

[0042] The guide member 8B of Fig. 5 also includes a rod-like guide 9B that extends vertically relative to the vehicle body along the C pillar 7, and the upper and low-

er fixing sections 10 and 11 for fixing the upper and lower ends of the guide 9B to the C pillar 7, respectively, and the temporarily tacking sections 12 and 13 for tacking both the upper and lower fixing sections 10 and 11 to the C pillar 7, respectively, when the guide member 8B is mounted to the C pillar 7. The rear end of the curtain airbag 1 is connected to the guide member 8B such that the loop-like connecting band 14 attached to the vicinity of the lower corner of the rear end is hooked around the guide 9B.

[0043] For the guide member 8B, a mooring section 40 is formed such that the lower part of the guide 9B which is substantially as high as the connecting band 14 of the curtain airbag 1 at the completion of inflation is bent forward (toward the curtain airbag 1) to form a loop.

[0044] Other structures of the guide member 8B are the same as those of the guide member 8 of Figs. 1 to 3, wherein in Fig. 5, the same reference numerals as those of Figs. 1 to 3 denote the same elements.

[0045] For the guide member 8B with such a structure, as the curtain airbag 1 is inflated to be deployed downward, the connecting band 14 is moved downward along the guide 9B, and when the curtain airbag 1 is inflated to substantially a maximum size, the connecting band 14 enters the mooring section 40. When the curtain airbag 1 has been fully inflated, the rear end of the curtain airbag 1 is pulled forward by tension applied to the outer surface, and also the connecting band 14 is pulled forward, thus being unable to come out from the mooring section 40. Accordingly, the rear end of the curtain airbag 1 is prevented from returning upward along the guide 9B.

[0046] A mooring section 41 of a guide member 8B' of Fig. 6 is formed such that the mooring section 40 of the guide member 8B of Fig. 5 is made of a radially plastically deformable material. Other structures are the same and the same reference numerals denote the same elements. For the guide member 8B', when the connecting band 14 enters the mooring section 41 as the curtain airbag 1 is deployed downward, and thereafter, the tension from the curtain airbag 1 is applied to the mooring section 41 through the connecting band 14, the mooring section 41 is pulled forward to be plastically deformed. Accordingly, the connecting band 14 is caught and secured by the mooring section 41 to prevent the rear end of the curtain airbag 1 from returning upward more reliably.

[0047] The embodiments described above are examples of the invention and the invention is not limited to the embodiments. For example, while the embodiments are constructed such that the C pillar 7 includes the guide member 8 to guide the rear end of the curtain airbag 1 downward relative to the vehicle body and along the C pillar 7 when the curtain airbag 1 is inflated. In the invention, however, the guide member may be provided to a B pillar or a D pillar. Alternatively, the guide member may be arranged at an A pillar to guide the front end of

the curtain airbag.

[Advantages]

- 5 [0048] As described in detail, according to the invention, there is provided a guide member for a curtain airbag which has remarkably high vehicle-installation efficiency. Also, according to the invention, it is also possible to prevent the end of the inflated curtain airbag from returning upward.

Claims

- 15 1. A guide member for a curtain airbag (1) for guiding the longitudinal ends of the curtain airbag (1) that is deployed downward along the side structure of the compartment of a vehicle, wherein
in the guide member (8; 8A; 8B; 8B') for the
20 curtain airbag (1) extending vertically and mounted to a pillar (7) of the vehicle,
each of the upper part and the lower part of the guide member (8; 8A; 8B; 8B') has a temporarily
25 tacking section (12; 13; 33) for tacking the guide member (8; 8A; 8B; 8B') to the pillar.
2. A guide member for a curtain airbag (1) according to Claim 1, wherein the temporarily tacking section (12; 13; 33) extends in a direction intersecting the longitudinal direction of the guide member (8; 8A; 8B; 8B').
- 30 3. A guide member for a curtain airbag (1) according to Claim 1 or 2, wherein a mooring section (9a; 40; 41) at the end of the curtain airbag (1) is formed such that the lower part of the guide member (8; 8A; 8B; 8B') is bent or curved so as to prevent the ends of the curtain airbag (1) which has moved downward along the guide member (8; 8A; 8B; 8B') from returning upward.
- 35 4. A guide member for a curtain airbag (1) for guiding the longitudinal ends of the curtain airbag (1) which is deployed downward along the side structure of the compartment of a vehicle, wherein
in the guide member (8; 8A; 8B; 8B') for the
40 curtain airbag (1) extending vertically and mounted to a pillar (7) of the vehicle,
a mooring section (9a; 40; 41) at the end of the curtain airbag (1) is formed such that the lower part of the guide member (8; 8A; 8B; 8B') is bent or curved so as to prevent the ends of the curtain airbag (1) which has moved downward along the guide member (8; 8A; 8B; 8B') from returning upward.
- 45 55




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 03 01 5531

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
Y	EP 0 955 213 A (BAYERISCHE MOTOREN WERKE AG) 10 November 1999 (1999-11-10)	1-3	B60R21/16
X	* column 3, line 1 - line 42; figure 1 *	4	
Y	US 5 951 046 A (KONISHI TOSHIYUKI ET AL) 14 September 1999 (1999-09-14)	1-3	
	* column 3, line 9 - line 61; figures 1,3-15 *		
Y	US 6 237 938 B1 (BOXEY KEVIN J) 29 May 2001 (2001-05-29)	1,2	
	* column 2, line 41 - line 50; figures 1,3 *		
Y	EP 0 642 957 A (SCHMIDT GMBH R) 15 March 1995 (1995-03-15)	1,2	TECHNICAL FIELDS SEARCHED (Int.Cl.7) B60R
	* column 5, line 18 - line 48; figures 1,4 *		
Y	WO 01 32474 A (BREED AUTOMOTIVE TECH) 10 May 2001 (2001-05-10)	1,2	
	* page 14, paragraph 3; figure 7 *		
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 3 November 2003	Examiner DE ACHA GONZALEZ, J
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 (03.02) (PAC01)



European Patent
Office

Application Number
EP 03 01 5531

CLAIMS INCURRING FEES

The present European patent application comprised at the time of filing more than ten claims.

- ☐ Only part of the claims have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims and for those claims for which claims fees have been paid, namely claim(s):
- ☐ No claims fees have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims.

LACK OF UNITY OF INVENTION

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

see sheet B

- ☐ All further search fees have been paid within the fixed time limit. The present European search report has been drawn up for all claims.
- ☒ As all searchable claims could be searched without effort justifying an additional fee, the Search Division did not invite payment of any additional fee.
- ☐ Only part of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the inventions in respect of which search fees have been paid, namely claims:
- ☐ None of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the invention first mentioned in the claims, namely claims:



European Patent
Office

**LACK OF UNITY OF INVENTION
SHEET B**

Application Number
EP 03 01 5531

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

1. Claims: 1-3

Guide member for curtain airbag with a temporarily tacking section for tacking it to a pillar of the vehicle.

2. Claim : 4

Guide member for curtain airbag comprising a mooring section formed by bending the lower part of the guide member so as to prevent the ends of the curtain airbag from returning upward after inflation.

The two independent claims 1 and 4 are solving different problems with different special technical features. Therefore the application is not unitary according to Article 82 EPC.

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 03 01 5531

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

03-11-2003

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
EP 0955213	A	10-11-1999	DE	19820568 A1	11-11-1999
			DE	59903284 D1	12-12-2002
			EP	0955213 A1	10-11-1999

US 5951046	A	14-09-1999	JP	10217905 A	18-08-1998
			DE	19804849 A1	06-08-1998

US 6237938	B1	29-05-2001	NONE		

EP 0642957	A	15-03-1995	DE	9400638 U1	17-03-1994
			DE	9313577 U1	21-10-1993
			DE	59404461 D1	04-12-1997
			DE	59408374 D1	08-07-1999
			EP	0642957 A2	15-03-1995
			EP	0761512 A1	12-03-1997
			ES	2132831 T3	16-08-1999

WO 0132474	A	10-05-2001	US	6412810 B1	02-07-2002
			EP	1286867 A2	05-03-2003
			WO	0132474 A2	10-05-2001

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82